



tesa® Adhesive Nail for Wallpaper & Plaster 1kg



Product Information

BNR 77773

Product Description

Adhesive Nail for up to 1kg. Ideal for hanging decorative items like pictures on textured and sensitive surfaces like wallpaper or plaster.

Caratteristiche

- For textured and sensitive surfaces like wallpaper or plaster
- For objects up to 1kg* per nail or 2kg using 2 nails
- Removable without a trace
- Reusable with a new strip

*For optimal results please read instruction leaflet

Application Fields

How to apply – Step by step1. Ensure the best possible bond by cleaning the surface of dirt and dust with a dust-free cloth.

2. Apply the Adhesive Strip to the rougher surface. In the case of wallpaper or plaster, always first apply it to the wall, with the blue tab facing the wall. Before using, make sure that your surface is strong enough to take the weight of the object you want to attach.

3. Press down evenly over the entire strip for at least 5 seconds and only then remove the protective foil. By pressing down like this, the flexible polymer chains are activated to form U-shaped links with the surface. It's these links that give such a secure and reliable bond, so the harder and more evenly you press, the better the bond.

4. Now apply the tesa® Adhesive Nail by aligning it on the top edge of the strip then folding it down. Press down evenly all over the entire nail for at least 5 seconds.

5. The tab should be left accessible behind your object or beneath the nail for easy removal.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|---|------------------|------------------|------|
| • Massa adesiva | synthetic rubber | • Senza silicone | yes |
| • Forza di adesione della striscia fino a | 1 Kg | • Tenuta fino a | 1 Kg |



tesa[®] Adhesive Nail for Wallpaper & Plaster 1kg

Product Information

Proprietà/Valori di prestazione

• Application temperature from	-15 °C	• Resistenza ad agenti chimici	no
• Area d'uso	Indoor	• Resistenza all'ozono	no
• Batterie incluse	no	• Resistenza all'umidità	no
• Batterie richieste	no	• Resistenza massima alla temperatura	35 °C
• Materiale	PS (polistirolo)	• Resistenza min. alle temperature	5 °C
• Materiale pericoloso	no	• Rimozione senza residui	yes
• Privo di solventi	yes	• Riutilizzabile	yes
• Resistente agli oli e lubrificanti	no	• Riutilizzabile con	Adhesive Strip 1kg Wallpaper
• Resistente ai raggi UV	no	• Superfici adatte	Wallpaper, Plaster
• Resistente all'acqua	no		

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>