



tesa® Professional 60953 Anti-slip Fluorescent



Product Information

Glow in the dark tape with anti slip effect

Product Description

The application area for tesa® Anti Slip Professional range is everywhere safe footing is required. Anti Slip fluorescent is the ideal protection to prevent from skidding and therefore helps to avoid accidents in the job related. Very good adhesion of the product is suitable for demanding surfaces such as factory floors, industry areas etc. The strong and durable adhesive coating secures a high Anti Slip effect of up to 1- 2 years in normal use areas. The Anti Slip tapes are hand tearable and no shrinkage occurs after application. The phosphorescent tape 60953 creates safe footing in shaded, or even totally dark surroundings / rooms.

Product Features

- The strong and durable adhesive coating secures a high Anti Slip effect of up to 1- 2 years in normal use areas.
- The Anti Slip tapes are hand tearable and no shrinkage occurs after application
- It creates safe footing in shaded, or even totally dark surroundings / rooms

Application Fields

- Indoor and outdoor applications * Applications in which a secure grip underfoot is required * Fluorescent (tesa® 60953): stays bright for a long period for safety and warning purposes in dark rooms * Transparent (tesa® 60952): make valuable surfaces such as wooden stairs, for example, safe unobtrusively * Black-yellow (tesa® 60951): marking of very slippery surfaces

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|----------------------------------------|----------------------|--------|
| • Backing material | PVC film coated with mineral particles | • Thickness of liner | 180 µm |
| • Type of adhesive | acrylic | • Thickness of tape | 720 µm |
| • Total thickness | 900 µm | | |



tesa[®] Professional 60953 Anti-slip Fluorescent

Product Information

Properties/Performance Values

• Elongation at break	25 %	• Fluorescent	yes
• Tensile strength	30 N/cm	• Fogging	low
• Abrasion resistance	very good	• Hand tearability	good
• Ageing resistance (UV)	good	• Humidity resistance	good
• Chemical resistance	good	• Suitable for die cutting	yes
• Easy to remove	no	• Temperature resistance short term duration	50 °C
• Easy to write on	no	• Water resistance	good

Adhesion to Values

- steel 5.8 N/cm

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=60953>