



tesa[®] 4378 Auto

Produkt Information

3-in-1-Lösung für schnelles, großflächiges Abdecken bei Lackierarbeiten mit anschließender Trocknung bis 120°C

Produktbeschreibung

tesa[®] 4378 Easy Cover[®] Auto is a 3-in-1 system for masking large areas for car body repair. The convenient system is comprised of the slightly crepe paper masking tape tesa[®] 4309 with natural rubber adhesive, a masking paper border and HDPE masking film, working together to ensure optimal protection. tesa[®] 4309 is a conformable and flexible paper masking tape. It is suitable for spray-painting applications, with subsequent oven-drying up to a temperature of 120°C.

Produktmerkmale

- Ideal for masking large areas easily and quickly
- Temperature resistance up to 120°C
- Additional masking paper border providing excellent paint absorption
- Reduction of logistic complexity
- tesa[®] 4378 Easy Cover[®] Auto allows a single person to cover large areas easily and quickly as well as reducing the logistic complexity.
- It is specifically treated for better paint adherence and clings to the car body.
- The additional masking paper border provides excellent paint absorption at the most critical area close to the repair spot.
- The HDPE film serves for the protection against spray particles.

Anwendung

- tesa[®] 4378 Easy Cover[®] Auto is recommended for professional masking during spray painting work for industrial applications and car body repair
- The 3-in-1 system is ideal for masking large areas easily and quickly for the protection against spray particles
- tesa[®] 4378 Easy Cover[®] Auto can withstand temperatures of up to 120°C

Technische Informationen (Durchschnittswerte)

Die Werte in diesem Abschnitt sind nur als repräsentativ oder typisch anzusehen und sind für die Verwendung in Spezifikationen nicht geeignet.

Produktaufbau

- | | | | |
|------------------|-------------------------|---------|--------|
| • Trägermaterial | leicht gekreptes Papier | • Dicke | 170 µm |
| • Klebmasse | Naturkautschuk | | |



tesa[®] 4378 Auto

Produkt Information

Eigenschaften / Leistungswerte

- | | | | |
|-------------------|---------|-------------------------------------|---------------------|
| • Reißdehnung | 12 % | • Dicke der Abdeckmaske | 10 µm |
| • Reißkraft | 47 N/cm | • Einfach zu entfernen | ja |
| • Abdeckmaske aus | HDPE | • Gewicht des zuzstl. Schutzpapiers | 37 g/m ² |

Klebkraft

- auf Stahl 3,5 N/cm

Haftungsausschluss

Die Qualität der tesa[®] Produkte wird kontinuierlich auf höchstem Niveau geprüft und ist deshalb strengen Kontrollen unterworfen. Alle obenstehenden technischen Informationen und Daten werden von uns nach bestem und auf praktischer Erfahrung beruhendem Wissen erteilt. Sie stellen Durchschnittswerte dar und sind nicht für eine Spezifikation geeignet. Daher kann die tesa SE weder ausdrücklich noch konkludent eine Gewährleistung geben, dies gilt insbesondere auch für die Marktgängigkeit und die Eignung für einen bestimmten Zweck. Der Benutzer selbst ist für die Entscheidung verantwortlich, ob ein tesa[®] Produkt für einen bestimmten Zweck und für die Anwendungsart des Benutzers geeignet ist. Falls Sie dabei Hilfe brauchen sollten, steht Ihnen unser technisches Personal mit einer entsprechenden Beratung gern zur Verfügung.



Für aktuelle Informationen zu diesem Produkt besuchen Sie <http://l.tesa.com/?ip=04378>