

tesa[®] Adhesive Nail for Wallpaper & Plaster 0.5kg



Product Information

BNR 77772

Product Description

Adhesive Nail for up to 0.5kg. Ideal for hanging decorative objects like pictures on textured and sensitive surfaces like wallpaper or plaster.

Caratteristiche

- · For textured and sensitive surfaces like wallpaper or plaster
- For objects up to 0.5kg* per nail or 1kg using 2 nails
- Removable without a trace
- Reusable with a new strip

*For optimal results please read instruction leaflet

Application Fields

How to apply - Step by step1. Get the most out of each Adhesive Strip by cleaning the surface of dirt and dust with a dustfree cloth.

2. First, apply the Adhesive Strip to the rougher surface (so in the case of wallpaper or plaster, always apply it to the wall) with the blue tab facing the wall. Before using, make sure that your surface is strong enough to take the weight of the object you want to attach.

3. Press down evenly over the entire strip for at least 5 seconds and only then remove the protective foil. Pressing down like this activates the flexible polymer chains that form U-shaped links with the surface. It's these links that give such a secure and reliable bond, so the harder and more evenly you press, the better the bond.

4. Now apply the tesa® Adhesive Nail by aligning it on the top edge of the strip, then folding it down. Press down evenly all over the entire nail for at least 5 seconds.

5. The tab should be left accessible behind your object or under the nail for easy removal.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

Massa adesiva

fino a

synthetic rubber Forza di adesione della striscia 0.5 Kg

 Senza silicone • Tenuta fino a

ves 0.5 Kg



tesa[®] Adhesive Nail for Wallpaper & Plaster 0.5kg

Product Information

Proprietà/Valori di prestazione

•	Application temperature from	-15 °C
•	Area d'uso	Indoor
•	Batterie incluse	no
•	Batterie richieste	no
٠	Materiale	PS (polistirolo)
٠	Materiale pericoloso	no
•	Privo di solventi	yes
٠	Resistente agli oli e lubrificanti	no
٠	Resistente ai raggi UV	no
٠	Resistente all'acqua	no

Resistenza ad agenti chimici	no
 Resistenza all'ozono 	no
 Resistenza all'umidità 	no
 Resistenza massima alla 	35 °C
temperatura	
Resistenza min. alle	5 °C
temperature	
Rimozione senza residui	yes
 Riutilizzabile 	yes
 Riutilizzabile con 	Adhesive Strip 0,5kg
	Wallpaper
Superfici adatte	Wallpaper, Plaster

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

