



tesa[®] Powerstrips

Product Information

BNR 57578, 57577

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|-----------------|------------------|------------------|------|
| • Massa adesiva | synthetic rubber | • Senza silicone | yes |
| • Forma gancio | Round | • Tenuta fino a | 1 Kg |

Proprietà/Valori di prestazione

- | | | | |
|--------------------------------------|------------------|---------------------------------------|----------------------------|
| • Application temperature from | +15 °C | • Resistente all'acqua | no |
| • Area d'uso | Indoor | • Resistenza ad agenti chimici | no |
| • Batterie incluse | no | • Resistenza all'ozono | no |
| • Batterie richieste | no | • Resistenza alla temperatura | yes |
| • Campo di applicazione | Cucina, Bagno | • Resistenza massima alla temperatura | 35 °C |
| • Materiale | PS (polistirolo) | • Resistenza min. alle temperature | 15 °C |
| • Materiale pericoloso | no | • Rimozione senza residui | yes |
| • Privo di solventi | yes | • Riutilizzabile | yes |
| • Resistente agli oli e lubrificanti | no | • Riutilizzabile con | Powerstrips Small |
| • Resistente ai raggi UV | no | • Superfici adatte | piastrelle smaltate, Vetro |
| • Resistente all'acqua | no | • Temperatura di applicazione di | +35 °C |
| • Resistente all'umidità | no | | |

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>