



# tesamoll® UNIVERSAL door-to-floor foam

## Product Information

BNR 05422

## Product Description

tesamoll® UNIVERSAL Door-to-Floor Foam is a cost-effective alternative to brush-type door draught stoppers. It is able to seal door-to-floor gaps up to 20 mm.

## Caratteristiche

- Stops draughts, dust, cold, warmth, noise and insects
- For even floors
- Quick and easy to apply
- Long-lasting

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## Product Construction

- |                 |          |                  |       |
|-----------------|----------|------------------|-------|
| • Supporto      | PVC foam | • Per fessure da | 20 mm |
| • Massa adesiva | acrylic  |                  |       |

## Proprietà/Valori di prestazione

- |                         |               |                                       |        |
|-------------------------|---------------|---------------------------------------|--------|
| • Batterie incluse      | no            | • Resistenza ad agenti chimici        | no     |
| • Batterie richieste    | no            | • Resistenza alla temperatura         | yes    |
| • Campo di applicazione | A casa, Porta | • Resistenza massima alla temperatura | 40 °C  |
| • Durata                | 2 years       | • Resistenza min. alle temperature    | -20 °C |
| • Materiale             | PVC           | • Rimozione senza residui             | no     |
| • Privo di solventi     | yes           |                                       |        |



# tesamoll<sup>®</sup> UNIVERSAL door-to-floor foam

Product Information

## Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>