



tesa[®] Adhesive nail canvas for wallpaper and plaster 2kg

Product Information

BNR 77779

Product Description

The adjustable adhesive nail for wallpaper & plaster is ideal for mounting a canvas securely and quickly without drilling. Moreover, it can be taken off without a trace and reused.

Caratteristiche

- Adjustable adhesive nail for sensitive surfaces
- Attaching stretcher frames and canvases without drilling
- Holds objects of up to 2kg per nail (4kg for two nails)
- Easy On & Off: no tools, removable without a trace
- Reusable with a new adhesive strip

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|---|------------------|------------------|------|
| • Massa adesiva | synthetic rubber | • Senza silicone | yes |
| • Forza di adesione della striscia fino a | 2 Kg | • Tenuta fino a | 2 Kg |

Proprietà/Valori di prestazione

- | | | | |
|--------------------------------------|------------------|---------------------------------------|---------------------------------|
| • Application temperature from | -15 °C | • Resistenza ad agenti chimici | no |
| • Area d'uso | Indoor | • Resistenza all'ozono | no |
| • Batterie incluse | no | • Resistenza all'umidità | no |
| • Batterie richieste | no | • Resistenza massima alla temperatura | 35 °C |
| • Materiale | PS (polistirolo) | • Resistenza min. alle temperature | 5 °C |
| • Materiale pericoloso | no | • Rimozione senza residui | yes |
| • Privo di solventi | yes | • Riutilizzabile | yes |
| • Resistente agli oli e lubrificanti | no | • Riutilizzabile con | Adhesive Strip 1kg
Wallpaper |
| • Resistente ai raggi UV | no | • Superfici adatte | Wallpaper, Plaster |
| • Resistente all'acqua | no | | |



tesa[®] Adhesive nail canvas for wallpaper and plaster 2kg

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>