



tesa[®] PRO 66957

Mounting PE-fixation

Product Information

tesa PRO Mounting PE-fixation - Strong and durable tape - Secure mounting - Ideal for indoor and outdoor use - Suitable for multiple application

Product Description

tesa PRO Mounting PE-fixation Get high immediate adhesion jobs on numerous substrates with tesa PRO Mounting PE-fixation. Suitable for POS-, exhibition sample displays, shelf edge labels, cable channels, window bars and window skirting trims, decorative glass or mirror elements in indoor spaces. holds objects in place even at low bonding pressure. Thanks to its extra length, never run out of tape again! The strong double-sided adhesive tape is UV-, water and ageing resistant. Easy to apply: Make sure the surface is dust and dirt-free. Press firmly for five seconds.

Product Features

- Durable and resistant: This professional tape is UV-, water- and ageing-resistant - high immediate bonding strength *
- Reliable grip without damaging the wall structure: tesa PRO Mounting PE-fixation doesn't require the use of screws, plugs or nails- for fast and long-lasting solutions with no tools necessary *
- Strong and versatile: Ideal for indoor and outdoor use - suitable for multiple applications, such as POS displays and exhibition sample displays and on various surfaces including materials like glass *
- Easy to use: The mounting tape can be cut into individual small or large pieces for an adhesive strip in the optimized size *
- Scope of delivery: 1 x tesa PRO Mounting PE-fixation tape - High immediate bonding strength - Indoor and outdoor use

Application Fields

Easy to apply:

- In order for the mounting tape to develop its full holding power, the object and surface must be free of dust, dirt and grease
- Don't touch the open adhesive surface as it could impair the adhesive strength
- Press firmly for five seconds
- For removal, carefully pull the mounting tape parallel from the wall
- As the mounting tapes are intended for permanent use, material residues may remain on the object. Try to remove with tesa adhesive remover

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|-------------------|-------------------|---------|
| • Backing | PE foam | • Total thickness | 1100 µm |
| • Type of adhesive | tackified acrylic | | |



tesa[®] PRO 66957 Mounting PE-fixation

Product Information

Properties/Performance Values

- | | | | |
|--------------------------|--------|-----------------------|-----------|
| • Tensile strength | 6 N/cm | • Chemical Resistance | good |
| • Ageing resistance (UV) | good | • Humidity resistance | very good |

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?mp=66957>