



tesa[®] 60422 PVO



Product Information

Heavy duty carton sealing tape

Product Description

tesa[®] 60422 is a premium packaging tape based on a very strong PVC backing and a natural rubber adhesive. Even heavy boxes or boxes with multiframe cardboard with high flap tension can be closed safely. The tensile strength and elongation characteristics of the backing make the product resistant to high shock impacts.

Product Features

- Good adhesion even in recycled cartons
- Excellent tack and long-lasting adhesion
- Silent unwinding
- Ideal for storage in extreme temperature conditions and high moisture

Application Fields

- Carton sealing of very heavy cartons or boxes with hazardous content
- Packaging, bundling and closing
- Brand showcase and advertisement purposed (printability)

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|----------------|-------------------|-------|
| • Backing | PVC film | • Total thickness | 88 µm |
| • Type of adhesive | natural rubber | | |

Properties/Performance Values

- | | | | |
|-----------------------|---------|-------------------------|-----|
| • Elongation at break | 100 % | • Automatic application | yes |
| • Tensile strength | 72 N/cm | • Manual application | yes |

Adhesion to Values

- | | |
|---------|--------|
| • Steel | 2 N/cm |
|---------|--------|

Additional Information

tesa[®] 60422 is easily printable.

Available colours: havana/chamois.

For latest information on this product please visit <http://l.tesa.com/?ip=60422>



tesa[®] 60422 PV0

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=60422>