

tesa® Professional 60021

Product Information

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

Silicone free yes

Properties/Performance Values

 Ad 	lhesive strength	Light adhesion	•	Reusable	no
 Ap 	plicationfield	Office, Home	•	Solvent free	no
• Ba	tteries included	no	•	Suitable for children of 3 years	no
• Ba	tteries required	no		of age	
• Ch	emical resistance	yes	•	Suitable surfaces	Even wood, Stone,
 Co 	mpostable	no			Brick, Acrylic glass
• Ec	ofriendly packaging	no	•	Temperature resistance	yes
 Ha 	zard material	yes	•	Temperature resistance max.	60 °C
• Hu	ımidity resistance	yes	•	Temperature resistance min.	-20 °C
 Re 	commended distance of	30 cm	•	UV resistant	yes
spi	raying		•	Washable	no
• Re	sidue free removal	no	•	Waterproof	yes

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

