



# tesa<sup>®</sup> 53123

## Product Information

### General Purpose Masking Tape

#### Product Description

tesa<sup>®</sup> 53123 is a creamed colored universal use paper masking tape suited for various non-critical applications. It is frequently used for masking indoors, light duty spray painting, bundling, fixation, packaging and label.

#### Features & Benefits:

- Tear resistant backing provides demasking in one piece
- Excellent adherence of paints and fillers
- Good peel adhesion provides secure bond on different substrates
- Residue free removal up to 3 days indoor
- Temperature resistance up to 60°C / 1 h and 80°C / 0,5h
- Consistent tesa Quality

#### Application Fields

Suitable for all non-critical general purpose masking, bundling, packaging and carton sealing applications.

#### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

#### Product Construction

- |                    |                       |                   |        |
|--------------------|-----------------------|-------------------|--------|
| • Backing          | slightly-creped paper | • Total thickness | 135 µm |
| • Type of adhesive | natural rubber        |                   |        |

#### Properties/Performance Values

- |                       |         |                    |           |
|-----------------------|---------|--------------------|-----------|
| • Elongation at break | 10 %    | • Easy to remove   | yes       |
| • Tensile strength    | 27 N/cm | • Hand tearability | very good |

#### Adhesion to Values

- |         |          |
|---------|----------|
| • Steel | 2.6 N/cm |
|---------|----------|



# tesa<sup>®</sup> 53123

## Product Information

### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=53123>