



tesa[®] 52310 PV7



Product Information

100µm Filmic tape

Product Description

tesa[®] 52310 PV7 is a 100µm thick filmic double sided tape specially suitable for compressible sleeves and thin plates (.045" or 1,14mm) in flexographic printing.

The unique properties of tesa[®] 52310 PV7 1000µm make it the ideal choice for high quality printing, easier demounting of plates without damaging them and clean removal from the sleeves without leaving residues.

Adhesive properties

- Secure bonding to sleeve, with specially enhanced removal properties allowing easy demounting of the plate
- Specially enhanced removal properties of the tape allowing the tape to be removed without leaving residues.

Additional properties

- The structured PP-liner prevents the formation of air pockets during plate mounting

Application Fields

The mounting of thin flexographic printing plates (<1,70mm / <.067") on compressible sleeves

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|----------------|-----------------|----|
| • Backing | PVC film | • Type of liner | PP |
| • Type of adhesive | natural rubber | | |

Properties/Performance Values

- | | |
|----------------------|-----|
| • Thickness category | 100 |
|----------------------|-----|



tesa[®] 52310 PV7

Product Information

Additional Information

52310 PV7 has been designed for the mounting of thin flexographic printing plates on compressible sleeves allowing easier demounting of the plates and residue free removal.

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=52310>