



51036 PV9 A



Product Information

PET cloth Sleeve for enhanced flexibility

Product Description

tesa Sleeve® 51036 PV9 is a PET cloth coated at the edges with an advanced acrylic adhesive (Triple A®) for lengthwise application.

Major Features:

- High temperature resistance 150°C/3000h
- High flexibility
- Abrasion resistant
- Easy and efficient lengthwise application

Color: Black

Applications

tesa Sleeve® 51036 PV9 is designed for the engine compartment, providing high flexibility.
For lengthwise application

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Applications

- | | | | |
|--------------------|-----------|-------------------|--------|
| • Backing | PET cloth | • Total thickness | 220 µm |
| • Type of adhesive | acrylic | | |

Properties/Performance Values

- | | | | |
|---|---------|-------------------------------|--------|
| • Abrasion resistance (10mm mandrel, LV312) | Class C | • Temperature resistance max. | 150 °C |
| • Abrasion resistance (5mm mandrel, LV312) | Class B | • Temperature resistance min. | -40 °C |
| • Noise damping (LV312) | Class A | | |

Adhesion to Values

- | | |
|---------|--------|
| • Steel | 5 N/cm |
|---------|--------|

Additional Information

Standard widths: 68, 78, 100, 130, 155, 195 mm
Standard lengths: 50 m

- Most combinations of width and length are possible

For latest information on this product please visit <http://l.tesa.com/?ip=51036>



51036 PV9 A

Product Information

Additional Information

- Also available with customized perforation

Harness diameter / tesa Sleeve® width recommendation

< Ø 13 mm / 68 mm > Ø 13 mm – 16 mm / 78 mm

Ø 16 mm – 23 mm / 100 mm

Ø 23 mm – 33 mm / 130 mm

Ø 33 mm – 41 mm / 155 mm

Ø 41 mm – 54 mm / 195 mm

- Standard core diameter: 76 mm

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=51036>