



# tesa<sup>®</sup> 4266

## Product Information



### General Purpose Carton Sealing

#### Product Description

tesa<sup>®</sup> 4266 is a polypropylene-based tape with an acrylic adhesive, used for general carton sealing and packaging applications. The packing tape is available in hand rolls and machine rolls and so can be used manually or with an automatic dispenser. It is ideal for high-volume applications on light- and medium-weight cartons. tesa<sup>®</sup> 4266 can be used at temperatures between -50°C and 100°C and is suitable for use on recycled board and under shrink wrap.

#### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

#### Product Construction

- |                    |                                |                   |       |
|--------------------|--------------------------------|-------------------|-------|
| • Backing          | PP film                        | • Total thickness | 55 µm |
| • Type of adhesive | synthetic rubber & epoxy resin |                   |       |

#### Properties/Performance Values

- |                         |         |                      |     |
|-------------------------|---------|----------------------|-----|
| • Elongation at break   | 130 %   | • Hand tearability   | low |
| • Tensile strength      | 52 N/cm | • Manual application | yes |
| • Automatic application | yes     |                      |     |

#### Adhesion to Values

- |         |          |
|---------|----------|
| • Steel | 2.6 N/cm |
|---------|----------|

#### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04266>