



# tesa<sup>®</sup> 4331

## Product Information



### High temperature masking tape

#### Product Description

tesa<sup>®</sup> 4331 is an extremely temperature resistant, flat back masking which offers the following qualities:

- strong adhesion and high thermal resistance
- achieves border-sharp coverage result
- removal without residues

#### Application Fields

- Masking during high stress electrostatic powder coating
- Steel furniture and hospital equipment
- tesa<sup>®</sup> 4331 sticks even to surface containing silicone

#### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

#### Product Construction

- |                    |                 |                   |        |
|--------------------|-----------------|-------------------|--------|
| • Backing          | PET / non-woven | • Total thickness | 110 µm |
| • Type of adhesive | silicone        |                   |        |

#### Properties/Performance Values

- |                       |         |                                   |        |
|-----------------------|---------|-----------------------------------|--------|
| • Elongation at break | 100 %   | • Hand tearability                | low    |
| • Tensile strength    | 53 N/cm | • Temperature resistance (60 min) | 200 °C |
| • Easy to remove      | yes     |                                   |        |

#### Adhesion to Values

- |         |        |
|---------|--------|
| • Steel | 4 N/cm |
|---------|--------|



# tesa<sup>®</sup> 4331

## Product Information

### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04331>