



tesa[®] 7009

Product Information

Double-sided Differential Adhesion Tape

Product Description

tesa[®] 7009 is a double-sided tape that features especially:

- High adhesion to the core
- Secure Adhesion to fluff pulp
- Unwinding of the fluff pulp without any residues on the pulp

Application Fields

tesa[®] 7009 is particularly suitable for:

- Core Starting of fluff pulp

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|-------------------|-------------------|-------------|
| • Backing | non-woven | • Total thickness | 285 µm |
| • Type of adhesive | tackified acrylic | • Color | translucent |

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=07009>