



tesa® 61114

Product Information



Neoprene closed cell single sided foam tape 6.4mm thick (black)

Product Description

tesa® 61114 is a 6.4mm thick black neoprene foam tape with a natural rubber adhesive on one side. The closed cell foam offers outstanding resistance to oils and other petrochemicals and is compatible with most plastics. tesa® 61114 is flame retardant to FMVSS302 and complies with automotive industry standards. The product also creates an electrolysis barrier between different metals, making it suitable for enclosure type applications, particularly where contact with oil and petrol will occur. The tape is also available in other thicknesses: 1.6 mm (tesa® 61111), 3.2 mm (tesa® 61112), 4.8 mm (tesa® 61113), 9.5 mm (tesa® 61115) and 12.7 mm (tesa® 61116).

Application Fields

- tesa® 61114 foam tape is well suited for sealing in transport applications due to its high resistance to petrol and oil. The product is commonly used in sealing applications in trucks, buses, special-purpose vehicles, boats, yachts and caravans
- Sealing access panel doors in machinery and transportation vehicles
- Sealing electrical enclosures and switch cabinets
- Sealing hatches on boats and yachts
- Sealing industrial access doors and hatches
- Sealing exterior and interior lighting

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|-----------|----------------------|--------------------|----------------|
| • Backing | Neoprene rubber foam | • Type of adhesive | natural rubber |
|-----------|----------------------|--------------------|----------------|

Properties/Performance Values

- | | | | |
|-----------------------|-----------|-------------------------------|-----------|
| • Elongation at break | 175 % | • Temperature resistance max. | 70 °C |
| • Chemical Resistance | very good | • Temperature resistance min. | -40 °C |
| • Compression Set | 9 % | • Water resistance | very good |
| • Hardness - Shore 00 | 37 STK | | |

Adhesion to Values

- | | |
|---------|---------|
| • Steel | 12 N/cm |
|---------|---------|



tesa[®] 61114

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=61114>