

tesa® 50020 Basic

Product Information

Basic TPP reinforcement tape

Product Description

tesa® 50020 Basic is a transparent tensilised polypropylene tape with a natural rubber adhesive.

tesa® 50020 Basic exhibits good tensile strength with low elongation at the same time and is highly conformable.

The product is especially recommended for basic reinforcement applications.

Basic reinforcement of corrugated and solid boards includes the reinforcement of flap and top hole handles from inside and outside of the box.

Application Fields

Basic reinforcement of corrugated and solid boards includes the reinforcement of flap and top hole handles from inside and outside of the box (transparent tape).

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

BackingType of adhesive	MOPP natural rubber	•	Total thickness	72 µm
Properties/Performance Values				
Elongation at breakTensile strength	40 % 180 N/cm	•	Can be cut/punched	no

Adhesion to Values

Steel 3 N/cm





tesa® 50020 Basic

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



Page 2 of 2 – as of 12/11/24 – en-AU