




tesa® 60412

90% Post Consumer Recycled PET Packaging Tape



Product Information

Recycled Polyester Packaging Tape

Product Description

tesa® 60412 is a sustainable packaging tape based on a 90% Post-Consumer Recycled (PCR) PET backing and a water-based acrylic adhesive system. tesa® 60412 has a strong and abrasion resistant backing with excellent bearing and wear properties. It features a very consistent, pressure sensitive acrylic adhesive, making this product the perfect solution for light- and medium-weight packaging application (max. 30 kg). The material combination guarantees a low noise unwind and an excellent printability with all types of ink systems.

tesa® 60412 not only provides an outstanding performance, but it is also an advanced alternative contributing to sustainability:

One step forward: This marker is our attempt to help you determine more sustainable products more easily.

Read more about it: Product Sustainability

- The backing material is made of post-consumer recycled PET (90% recycled content).
- This product can be disposed together with the box into the blue bin without endangering the cardboard recycling process (certified according to INGEDE method 12).
- The production process of this product is solvent-free

tesa® 60412 offers excellent performance on recycled cardboard

Sustainable Aspects

- Backing made with 90% recycled PET from post consumer waste
- Solvent-free production process
- Recycling friendly adhesive does not disturb the paper recycling process



For more information: <https://www.tesa.com/product-sustainability>

Product Features

- Backing made with 90% recycled post consumer waste
- Strong, tear and puncture resistant PET backing
- Versatile water based acrylic adhesive
- Smooth, silent unwinding
- Available in brown, white and transparent

For latest information on this product please visit <http://l.tesa.com/?ip=60412>



tesa® 60412

90% Post Consumer Recycled PET Packaging Tape

Product Information

Application Fields

- Sealing of cardboard boxes
- Suitable for light- and medium-weight packaging applications (max. 30 kg)
- Excellent adhesion in recycled cardboard
- Suitable for manual and automatic dispensers
- Brand showcase and advertising purposes through custom printing

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|---|------|--------------------|---------------------|
| • Backing | PET | • Type of adhesive | water-based acrylic |
| • Bio-based carbon content of liner (acc. DIN EN 16640) | 90 % | • Total thickness | 56 µm |

Product Assortment

- | | |
|--------------------|---------------------------|
| • Available colors | white, brown, transparent |
|--------------------|---------------------------|

Properties/Performance Values

- | | | | |
|-------------------------|---------|------------------------------|--------------------|
| • Elongation at break | 130 % | • Packaging Weight | Up to 30 kg |
| • Tensile strength | 60 N/cm | • Silent unwinding | yes |
| • Automatic application | no | • Suitable for deep freezing | yes |
| • Hand tearability | low | • Transport Information | Temperature 0-70°C |
| • Humidity resistance | yes | | |

Adhesion to Values

- | | |
|---------|--------|
| • Steel | 3 N/cm |
|---------|--------|

Certificates

Sustainability Certificates

- Tested according to INGEDE method 12. Test report available



tesa[®] 60412

90% Post Consumer Recycled PET Packaging Tape

Product Information

Additional Information

Available in transparent. Brown and white are available upon request.

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=60412>