




tesa[®] 6081

Product Information



Spool Dispenser with brake & buffer system

Product Description

Laminate trims and profiles continuously with double sided tape at high speed or stop & go processes

- Unwind tape from spools in a controlled way. Guide the tape precisely and without damage to the lamination unit.
- The brake and buffer system allows a high lamination speed and compensates for variations in line speed due to e.g. cutting processes.
- Easy operation and little set-up time translates into efficient processes.

Application Fields

The reliable taping process has been proven at many customers worldwide. Commonly used by producers of aluminium profiles, MDF trims, magnetic strips.

Properties/Performance Values

- Core diameter 6
- Roll width max 250 mm

Additional Information

Integrate the spool dispenser into your production line easily

- Easy mounting and retro-fitting to existing production lines.
- Modify to left or right hand production direction.
- Tape unwinding is done mechanically by the propulsion of the profile.
- Delivered ready-to-run without any electrical components.
- Ask for our tesa engineering support.

In the product manual you will find drawings of all sections and item listings. The only part which eventually needs to be replaced may be the brake belt. In case you need any spare parts please refer to this item listings and contact:

Nauber-Feinmechanik
Thomas-Mann-Str. 29
D-22175 Hamburg
Tel.: +49 40 / 640 14 16
Fax.: +49 40 / 640 76 92
info@nauber-feinmechanik.de



tesa[®] 6081

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=06081>