




tesa[®] ACXplus 7048

Product Information



High bond double sided acrylic foam tape 2mm thick

Product Description

tesa[®] ACX^{plus} 7048 is a double sided acrylic foam tape, consisting of a high-performance acrylic adhesive system and is primarily characterised by its bonding power and stress dissipation characteristics.

The viscoelastic core of this product is able to compensate thermal elongation of bonded parts. tesa[®] ACX^{plus} 7048 performs well on "hard-to-bond" materials such as powder coatings or plastic materials. The grey or white colour options adapt very well to metal and plastic surfaces, resulting in an invisible bond.

Application Fields

- tesa[®] ACX^{plus} 7048 is suitable for a wide range of constructive bonding applications including:
- Decorative panels (e.g. refrigerator glass doors)
- Decorative elements (e.g. covers of dishwashers, muntin bars on windows)
- Glass-to-glass or glass-to-metal applications (e.g. partition walls or glass doors)

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|----------------|-------------------|---------|
| • Backing | filled acrylic | • Total thickness | 2000 µm |
| • Type of adhesive | pure acrylic | | |

Adhesion to Values

- | | |
|------------------------|---------|
| • Steel (after 3 days) | 44 N/cm |
|------------------------|---------|



tesa[®] ACXplus 7048

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=07048>