tesa® Aluxx shower caddy, chromed aluminium, self-adhesive

Product Information

BNR 40201

Product Description

It's a breeze to apply the self-adhesive tesa® Aluxx shower caddy to a wall. No drilling is needed, so no surfaces are damaged. It can also be conveniently removed and put back up in another location with a new adapter BK43-2. Its glossy frame is stainless, providing a gorgeous spot for your shampoo or shower gel.

Product Features

* Shower caddy, with tesa® Power.Kit technology (all-in-one adhesive mounting solution)
* High gloss chrome-plated aluminum, round style, circular wall plates
* Reliable hold, waterproof, guaranteed stainless
* Works on tiles, metal, natural stone, marble, concrete, wood, glass and many types of plastic
* Does not work on wallpaper, stucco and other surfaces with non-stick coating
* Can be removed swiftly without a trace and attached in a different location with adapter BK43-2
* No drilling, simple fastening
* Product dimensions: 92mm x 250mm x 125mm

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Applications

• Type of adhesive	Silane modified polymer		• Hook shape	Round
• Holding power up to	5 Kg			

Properties/Performance Values

• Applicationfield	Bathroom		• Residue-free removability	yes
• Area of use	Indoor		• Reusable	yes
• Batteries included	no		• Reusable with	Adapter BK43-2
• Batteries required	no		• Shape of wall piece	Round
• Chemical Resistance	no		• Solvent free	yes
• Curing time	12 hour(s)		• Suitable surfaces	Glazed Tiles, Glass, Marble
• Design series	tesa® ALUXX			
• Hazard material	yes		• UV resistant	yes
• Material	Chromed aluminium		• Waterproof	yes

For latest information on this product please visit http://l.tesa.com/?cp=NaN

tesa® Aluxx shower caddy, chromed aluminium, self-adhesive

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit http://l.tesa.com/?cp=NaN