



Product Information

Premium Plastering Tape Orange

Product Description

tesa® 4843 is a specially formulated plasticised PVC tape with a flat backing, low unwinding force and high adhesion. Having a soft modified and thick rubber adhesive coating tesa® 4843 is suitable for most rough surfaces. The tape can withstand humidity, weak alkaline solutions, acids and many other chemicals. Once applied it can be easily removed even after 2 weeks of outdoor application without leaving any residue.

Application Fields

tesa[®] 4843 is suitable for masking during plastering, painting, gypsum, masonry and stucco work. It protects the surfaces of sensitive profiles and facings against dirt and damage through manufacturing tools and material. It is also suitable for the sealing of bags, heavy duty wrapping and other DIY applications. The tape can be used for temperatures above 0°C.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

Backing PVC film

Properties/Performance Values

Tear resistance

Temperature resistance yes

Adhesion to Values

Steel
1.2 N/cm

yes





Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



Page 2 of 2 – as of 12/11/24 – en-AU