



tesa® 64701

Product Information



High density PVC closed cell single sided foam tape 1.6mm thick (black). Ideal for use in the glazing market

Product Description

- The closed cell foam can create a waterproof barrier when compressed, while still being flexible enough to seal uneven surfaces.
- The higher density foam of tesa® 647 Series foam tapes has a great resistance to water penetration, making it the ideal choice for sealing applications in the glazing market.
- tesa® 647 series is resistant to UV.
- The product is available in customized die cuts.

Applications

tesa® 64701 foam tape is ideal for use in glazing, marine and transportation type applications, including bus, truck and caravan manufacturing.

Application ideas:

- Sealing between glass and aluminum in windows.
- Sealing the corners of aluminum window frames.
- Sealing between panels in trucks and buses.
- Sealing externally mounted air-conditioning fan units on walls and roofs.
- Sealing electrical access panels on industrial machinery.
- Sealing electrical housings, enclosures and cabinet doors.
- Sealing under glass stove-tops

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Applications

- | | | | |
|--------------------|----------|---------|-------|
| • Backing | PVC foam | • Color | black |
| • Type of adhesive | acrylic | | |

Product Assortment

- | | | | |
|--------------------|-------|-------------------------|--------|
| • Available colors | black | • Available thicknesses | 1.6 mm |
| • Available liners | paper | | |



tesa[®] 64701

Product Information

Properties/Performance Values

- | | | | |
|--------------------------|--------|-------------------------------------|-----------|
| • Elongation at break | 120 % | • Temperature resistance long term | 90 °C |
| • Tensile strength | 9 N/cm | • Temperature resistance short term | 105 °C |
| • Ageing resistance (UV) | good | • Water resistance | very good |

Adhesion to Values

- | | | | |
|-------------------|----------|-------------------------|--------|
| • Steel (initial) | 6.5 N/cm | • Steel (after 14 days) | 8 N/cm |
|-------------------|----------|-------------------------|--------|

Storage Conditions

Storage Conditions

Temperature: +5°C to +30°C

Relative humidity: 10% to 90%

Precautions: protect for direct sun light, do not store outside

Other storage advice: avoid mechanical impacts and short overheating

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=64701>