



Product Information



1600 µm

black

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

• Backing	PVC foam	•	Total thickness
 Type of adhesive 	acrylic	•	Color
Type of liner	paper		

Properties/Performance Values

•	Elongation at break Tensile strength	50 % 10 N/cm	•	Temperature resistance long term	90 °C
•	Ageing resistance (UV)	good	•	Temperature resistance short term	105 °C

Adhesion to Values

•	Glass (initial)	5 N/cm	•	Steel (initial)	6.5 N/cm
•	Glass (after 14 days)	7 N/cm	•	Steel (after 14 days)	8 N/cm

Storage Conditions

Storage Conditions

Temperature: +5°C to +30°C Relative humidity: 10% to 90% Precautions: protect for direct sun light, do not store outside Other storage advice: avoid mechanical impacts and short overheating





Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



Page 2 of 2 – as of 21/11/24 – en-AU

For latest information on this product please visit http://l.tesa.com/?ip=64802