



**Product Information** 



## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## **Product Construction**

<ul><li>Backing</li><li>Type of adhesive</li><li>Type of liner</li></ul>	aluminium foil acrylic paper	<ul><li>Total thickness</li><li>Color of liner</li><li>Thickness of liner</li></ul>	90 μm white 85 μm
Properties/Performan	ce Values		
<ul> <li>Elongation at break</li> </ul>	6%	<ul> <li>Hand tearability</li> </ul>	very good

<ul> <li>Elongation at break</li> </ul>	6 %	<ul> <li>Hand tearability</li> </ul>	very good
Tensile strength	40 N/cm	Liner release force	0.3 N/cm
<ul> <li>Backing appearance (visual)</li> </ul>	reflective	<ul> <li>Operation temperature from</li> </ul>	-40 °C
<ul> <li>Easy to remove</li> </ul>	no	<ul> <li>Operation temperature up to</li> </ul>	+160 °C
Adhasian ta Valuas			
Adhesion to Values			
Backing	9 N/cm	• PVC (initial)	6 N/cm
	9 N/cm 9 N/cm	<ul><li> PVC (initial)</li><li> Steel</li></ul>	6 N/cm 9 N/cm
• Backing			

## Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit http://l.tesa.com/?ip=60652