

tesa® 66712

Product Information



_NULL

Product Features

- · Non-staining, non-corrosive, non-conductive foam
- Resistant to moisture & UV
- Flame retardant to FMVSS 302
- Will not contaminate drinking water ¹
- REACH & RoHs compliant
- · Plastic compatible

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

•	Backing	EPDM rubber foam	• Color	black
•	Type of adhesive	acrylic		

Properties/Performance Values

•	Elongation at break	55 %	•	Temperature resistance min.	-40 °C
•	Tensile strength	18 N/cm	•	Thermal conductivity z-direction	0.05 W/mK
•	Hardness - Shore 00	40 STK	•	Water resistance	very good
•	Temperature resistance max.	115 °C			

Adhesion to Values

• Steel (initial) 5.5 N/cm

¹ EPDM foam backing tested according to FDA 21CFR 177.2600 (distilled water method)



tesa® 66712

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

