



# tesa® Professional 4348 Painters' Tape



## Product Information

Flexible masking tape for indoor painting applications

## Product Description

tesa® 4348 is a finely creped paper masking tape with a natural rubber adhesive.

## Product Features

- The supple masking tape can be torn by hand, used for up to 7 days, and is easy to remove after use.
- Thanks to its excellent adhesive strength, it enables clearly-defined edges during painting work and is a reliable tool for professional painters.

## Application Fields

- Indoor applications
- Clean edges to paint and lacquer
- For smooth surfaces
- For simple painting tasks

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## Product Construction

- |                    |                       |                   |            |
|--------------------|-----------------------|-------------------|------------|
| • Backing material | slightly-creped paper | • Total thickness | 140 µm     |
| • Type of adhesive | natural rubber        | • Colour          | pale cream |

## Properties/Performance Values

- |                       |         |                    |           |
|-----------------------|---------|--------------------|-----------|
| • Elongation at break | 10 %    | • Hand tearability | very good |
| • Tensile strength    | 36 N/cm |                    |           |

## Adhesion to Values

- |         |          |
|---------|----------|
| • steel | 3.3 N/cm |
|---------|----------|



# tesa<sup>®</sup> Professional 4348 Painters' Tape

## Product Information

### Additional Information

tesa<sup>®</sup> 4348 features a high immediate bond and can be removed without leaving any adhesive residue.

## Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04348>