



tesa[®] Professional 60100

Product Information

Fibreglass Tape / Plasterboard tape

Product Description

tesa[®] 60100 is a self-adhesive, flat and supple glass fibre tape that is coated with an acrylate adhesive mass. It is highly adhesive and can also be used on rough surfaces. The tear-resistant glass fibre tape provides painters and builders with a professional means of closing gaps in sheetrock panels or holes in walls. After being applied to dry and clean surfaces, a thin layer of putty can be applied and worked in immediately and dries very quickly, saving much time compared to traditional methods.

Product Features

- Closing gaps in sheetrock panels
- Fixing and patching small holes and cracks

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|------------|-------------------|--------|
| • Backing material | fibreglass | • Total thickness | 260 µm |
| • Type of adhesive | acrylic | | |

Properties/Performance Values

- | | | | |
|-----------------------|-----|--------------------|----------|
| • Elongation at break | 2 % | • Tensile strength | 102 N/cm |
|-----------------------|-----|--------------------|----------|

Adhesion to Values

- | | |
|---------|----------|
| • steel | 0.7 N/cm |
|---------|----------|



tesa[®] Professional 60100

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?mp=60100>