



tesa[®] 4378 Easy Cover[®] Auto

Product Information

3 in 1 - Car body masking solution for large areas

Product Description

tesa[®] 4378 Easy Cover Auto is a convenient “3 in 1” solution for the masking of large areas for car body repair. The system includes:

1. Masking tape tesa[®] 4309
2. Masking paper border
3. HDPE masking film

The main advantage is the combination of the advantages of the single components.

- a) tesa[®] 4309 is a finely creped, extremely stretchable and flexible paper masking tape. It is suitable for water and solvent based paints and can be used for paint spraying with subsequent oven/ or IR-drying up to a temperature of 120 °C.
- b) The additional paper edge provides perfect paint absorption on the most critical area close to the repair.
- c) The HDPE film protects against spray particles. It is specifically treated for better paint adherence. Due to the high static the film clings to the car body.

tesa[®] Easy Cover Auto allows one person to cover large areas easily and quickly. For storing, transporting and disposing of tesa[®] Easy Cover[®] Auto saves space.

Product Features

- Ideal for masking large areas easily and quickly
- Temperature resistance up to 120°C
- Additional masking paper border providing excellent paint absorption
- Reduction of logistic complexity
- tesa[®] 4378 Easy Cover[®] Auto allows a single person to cover large areas easily and quickly as well as reducing the logistic complexity.
- It is specifically treated for better paint adherence and clings to the car body.
- The additional masking paper border provides excellent paint absorption at the most critical area close to the repair spot.
- The HDPE film serves for the protection against spray particles.

Application Fields

- Professional masking applications during lacquering work
- Masking of large areas before car body repair jobs
- Protection against spray particles



tesa[®] 4378 Easy Cover[®] Auto

Product Information

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|-----------------------|-------------------|--------|
| • Backing material | slightly-creped paper | • Total thickness | 170 µm |
| • Type of adhesive | natural rubber | | |

Properties/Performance Values

- | | | | |
|-----------------------|---------|-------------------------------------|---------------------|
| • Elongation at break | 12 % | • Material of masking coverage | HDPE |
| • Tensile strength | 47 N/cm | • Thickness of masking coverage | 10 µm |
| • Easy to remove | yes | • Weight of addtl. protection paper | 37 g/m ² |

Adhesion to Values

- | | |
|---------|----------|
| • steel | 3.5 N/cm |
|---------|----------|

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04378>