



tesa[®] 51575

Product Information



Double-sided non-woven tape

Product Description

tesa[®] 51575 is a double-sided tape with a non-woven backing. It is coated with a water-based acrylic adhesive offering high tack, high shear and temperature resistance. The special adhesive formulation ensures a good bond even on rough surfaces such as cardboard and corrugated board.

Product Features

- The special adhesive formulation ensures a good bond even on rough surfaces like cardboard and corrugated board.
- It is coated with a water-borne acrylic adhesive offering high tack and high shear and temperature resistance.

Application Fields

General purpose mounting

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|---------------------|-------------------|---------------------|
| • Backing material | non-woven | • Total thickness | 90 µm |
| • Type of adhesive | water-based acrylic | • Colour | translucent |
| • Type of liner | glassine | • Weight of liner | 82 g/m ² |

Adhesion to Values

- | | |
|-------------------|----------|
| • Steel (initial) | 3.2 N/cm |
|-------------------|----------|



tesa[®] 51575

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=51575>