



tesa[®] 4331

Product Information



High temperature masking tape

Product Description

tesa[®] 4331 is an extremely temperature resistant, flatback masking tape which offers the following qualities:

- strong adhesion and high temperature resistance
- achieves sharp paint edges
- removal without residues

Product Features

- The tape enables sharp color edges and offers excellent paint anchorage.
- The masking tape's silicone adhesive system makes the tape extremely heat-resistant, withstanding extreme temperatures of up to 200°C for as long as 30 minutes at a time.
- Residue-free removability for masking applications
- High adhesion for secure bonding, even adheres to surfaces containing silicone

Application Fields

- Masking during high stress electrostatic powder coating
- Steel furniture and hospital equipment
- tesa[®] 4331 sticks to surfaces containing silicon

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|-----------------|-------------------|--------|
| • Backing material | PET / non-woven | • Total thickness | 110 µm |
| • Type of adhesive | silicone | | |

Properties/Performance Values

- | | | | |
|-----------------------|---------|--------------------|-----|
| • Elongation at break | 100 % | • Easy to remove | yes |
| • Tensile strength | 53 N/cm | • Hand tearability | low |

Adhesion to Values

- | | |
|---------|--------|
| • steel | 4 N/cm |
|---------|--------|



tesa[®] 4331

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04331>