



# tesa<sup>®</sup> 51917

## Product Information



Repulpable double-sided splicing tape

### Product Description

tesa<sup>®</sup> 51917 is a double-sided repulpable tape consisting of a tissue paper and a modified water based acrylic adhesive.

tesa<sup>®</sup> 51917 features:

- Highest tack properties
- Very good adhesion values on coated and uncoated papers
- Good shear strength
- Good repulpability over pH-range: pH3 –pH9

Colour: Blue, Colourless

### Application Fields

tesa<sup>®</sup> 51917 is particularly suitable for

- Flying splice processes with critical adherence conditions

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

- |                    |                              |                   |                              |
|--------------------|------------------------------|-------------------|------------------------------|
| • Backing material | non-woven                    | • Type of liner   | repulpable siliconised paper |
| • Type of adhesive | repulpable tackified acrylic | • Total thickness | 115 µm                       |

### Properties/Performance Values

- |                           |      |        |           |
|---------------------------|------|--------|-----------|
| • Static shear resistance | good | • Tack | very good |
|---------------------------|------|--------|-----------|



# tesa<sup>®</sup> 51917

## Product Information

### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=51917>