



tesa® 51609

Product Information



PET fleece wire harness tape for the passenger compartment optimized for automatic bundling

Product Description

tesa® 51609 is the universal tape for wire harness bundling in the passenger compartment. It combines important features as noise damping, abrasion resistance and bundling strength while keeping harnesses flexible supporting an easy harness assembly process at the OEM. tesa® 51609 is optimized for automatic wrapping equipment.

Features:

- noise dampening
- abrasion resistant
- flexible and smooth
- tear resistant
- stable and low unwind force
- resistant to ageing
- strong adhesion
- handtearable

Application Fields

Wire Harnessing

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|--------------|-------------------|--------|
| • Backing material | PET fleece | • Total thickness | 280 µm |
| • Type of adhesive | rubber based | | |

Properties/Performance Values

- | | | | |
|---|---------|-----------------------------------|---------------------|
| • Elongation at break | 20 % | • Temperature resistance max. | 105 °C |
| • Tensile strength | 40 N/cm | • Temperature resistance min. | -40 °C |
| • Abrasion resistance (10mm mandrel, LV312) | Class B | • Unwind force (roll width > 9mm) | 4 N/roll (30 m/min) |
| • Abrasion resistance (5mm mandrel, LV312) | Class A | • Unwind force (roll width ≤ 9mm) | 4 N/roll (30 m/min) |
| • Noise damping (LV312) | Class C | | |

For latest information on this product please visit <http://l.tesa.com/?ip=51609>



tesa[®] 51609

Product Information

Adhesion to Values

- steel 3 N/cm

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=51609>