



Sugru by tesa®

Product Information



BNR 41282, 41281, 41286, 41234, 41212, 41237, 41235, 41283, 41232, 41236, 41231, 41284, 41285, 41233, 41211, 41287

Product Description

Sugru Mouldable Glue by tesa, the world's first mouldable glue that turns into silicone rubber by itself.

Product Features

- Made for fixing, bonding, repairing, sealing, reinforcing, mounting without drilling, DIY ideas
- No mess: non-runny, non-toxic formula for quick and easy application (indoor & outdoor)
- Versatile: mouldable, waterproof, heat and cold-resistant, durable, electrically insulating
- Strong: holds up to 2kg on glass, ceramics, wood, metal, plaster, most plastics and some fabrics

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- Type of adhesive silicone based • Silicone free no



Sugru by tesa®

Product Information

Properties/Performance Values

• Abrasion resistance	yes	• Open & Closable up to	1 STK
• Adhesive strength	High adhesion	• Ozone resistance	yes
• Ageing resistance (UV)	yes	• Residue free removal	yes
• Application temperature from	-10 °C	• Reusable	no
• Area of use	In- and Outdoor	• Solvent free	yes
• Batteries included	no	• Suitable for children of 3 years of age	yes
• Batteries required	no	• Suitable surfaces	Most plastics, Glass, Cardboard, Carpets, Metal, Marble, Steel, Stone, Even wood, Tiles, Wooden floors, Brick, Acrylic glass, Paper, Fabrics, Concrete, Wallpaper
• Compostable	no		
• Durability	5+ years		
• Hazard material	no		
• Humidity resistance	yes		
• Material	Silicone		
• Mouldable	yes		
• Oil and grease resistance	no		
		• Temperature resistance	yes
		• Temperature resistance max.	180 °C
		• Temperature resistance min.	-40 °C
		• UV-resistant	yes
		• Washable	yes
		• Waterproof	yes

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>