



# tesa<sup>®</sup> 51344

## Product Information



Paper-based tear tape

## Product Description

Paper-based tear tape

## Sustainable Aspects



For more information: <https://www.tesa.com/product-sustainability>

## Product Features

- Strong paper backing and high adhesion on board material for reliable and quick box opening performance
- Homogenous visual appearance within final packaging
- Product design helps to achieve higher content of single source packaging material
- Smooth unwinding and proven processability on market standard tape applicators

## Application Fields

- For medium grades of corrugated board and heavy envelopes
- Recommended for automatic production

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## Product Construction

- |                    |                  |                   |        |
|--------------------|------------------|-------------------|--------|
| • Backing material | Paper            | • Total thickness | 220 µm |
| • Type of adhesive | synthetic rubber |                   |        |

## Properties/Performance Values

- |                         |          |                      |     |
|-------------------------|----------|----------------------|-----|
| • Elongation at break   | 12 %     | • Manual application | no  |
| • Tensile strength      | 145 N/cm | • Solvent free       | yes |
| • Automatic application | yes      |                      |     |

## Adhesion to Values

- |         |         |
|---------|---------|
| • steel | 11 N/cm |
|---------|---------|

For latest information on this product please visit <http://l.tesa.com/?ip=51344>



# tesa<sup>®</sup> 51344

## Product Information

### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=51344>