



tesa[®] 4104 colored

Product Information

Coloured packaging adhesive film to securely seal boxes

Product Description

tesa[®] 4104 is a premium packaging tape based on a PVC-film backing and a natural rubber adhesive. It shows excellent performance on all kinds of cardboard and provides a safe closure. The natural rubber adhesive system is designed to show best results for applications on different kind of surfaces.

Product Features

- The natural rubber adhesive system is designed to show best results for applications on different kind of surfaces.
- It shows excellent performance on all kind of cardboards and secures a safe closure.

Application Fields

- sealing small boxes (card-board or plastic)
- sealing tins and bags
- variety of colours available make tesa[®] 4104 ideal for marking
- tesa[®] 4104 red enables a sharp-edge when masking for multicolour painting.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|----------------|-------------------|-------|
| • Backing material | PVC film | • Total thickness | 67 µm |
| • Type of adhesive | natural rubber | | |

Properties/Performance Values

- | | | | |
|-----------------------|------|--------------------|---------|
| • Elongation at break | 60 % | • Tensile strength | 60 N/cm |
|-----------------------|------|--------------------|---------|

Adhesion to Values

- | | |
|---------|----------|
| • steel | 3.6 N/cm |
|---------|----------|



tesa[®] 4104 colored

Product Information

Additional Information

tesa[®] 4104 is easily printable. Available colours: black, white, red, orange, yellow, blue and green.

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04104>