

tesa® 60760 PV1

Product Information

Floor Marking Tape

Product Description

tesa® 60760 is a tough plasticised PVC tape coated with an aggressive modified rubber-resin adhesive which allows adhesion on many different surfaces. tesa® 60760 is also hand tearable.

Application Fields

tesa ® 60760 is perfectly suitable for temporary and low duty hazard warning & marking of any kind of mobile or static objects.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

• Backing material soft PVC • Total thickness 150 μm

Type of adhesive natural rubber

Properties/Performance Values

Elongation at break
Suitable for rough surfaces
very good

• Tensile strength 33 N/cm

Adhesion to Values

• steel 2 N/cm



tesa® 60760 PV1

Product Information

Additional Information

tesa @ 60760 is also available in two highly visible colour combinations in accordance with safety regulations.

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

