



52817

Secure



Product Information

Foam plate mounting tape

Product Description

Double sided foam tape

Foam Properties

- Low thickness tolerance
- Long lasting, constant recovery characteristics

Adhesive Properties

- Low tack surface characteristics
- Strong adhesion on both sides
- Solvent resistance

Additional Properties

- Structured PP liner
- Logo color indicates foam hardness

Product Features

- Foam Properties: Low thickness tolerance. Long lasting, constant recovery characteristics.
- Adhesive Properties: Low tack surface characteristics. Strong adhesion on both sides. Solvent resistance.
- Additional Properties: Structured PP liner. Logo color indicates foam hardness.

Application Fields

Mounting of 1.14 mm (0.45") and 1.70 mm (0.067") thickness, PET backing, flexographic printing plates onto steel / alu / PU and glassine cylinders and sleeves.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|------------------------------|-------------------|--------|
| • Backing material | PE foam with film lamination | • Type of liner | PP |
| • Type of adhesive | tackified acrylic | • Total thickness | 430 µm |

Properties/Performance Values

- | | | | |
|---------------|------|----------------------|-----|
| • Hardness | soft | • Thickness category | 380 |
| • Logo colour | red | | |

For latest information on this product please visit <http://l.tesa.com/?ip=52817>



52817 Secure

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=52817>