



tesa[®] 51134

Product Information



Surface protection and masking tape

Product Description

tesa[®] 51134 is a transparent self-adhesive polyethylene tape with an acrylic adhesive for masking large areas of plastic parts during professional painting processes.

Additionally tesa[®] 51134 can be used as an interior protection tape for slightly structured surfaces.

Product Features

- Transparent film with higher adhesion
- Good adhesion and traceless removal
- Versatile with regard to use on surfaces like PP, ABS, and textiles
- Cost saving due to reduction in rectification and final repair
- No special equipment needed, ensuring simple, low-cost application and removal processes

Application Fields

- Protection of various surfaces against dirt and damage

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|---------|-------------------|-------|
| • Backing material | PE film | • Total thickness | 84 µm |
| • Type of adhesive | acrylic | | |

Properties/Performance Values

- | | | | |
|-----------------------|---------|--------------------|------|
| • Elongation at break | 200 % | • Easy to remove | yes |
| • Tensile strength | 15 N/cm | • Flame retardance | good |

Adhesion to Values

- | | |
|---------|----------|
| • steel | 2.4 N/cm |
|---------|----------|



tesa[®] 51134

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=51134>