



tesa[®] extra Power Universal

Product Information



BNR 56348, 56338, 56389, 56388, 56380, 56490, 56396

Product Description

tesa[®] extra Power Universal is a versatile duct tape with high bonding power. Ideal for handicrafts, repairing, fastening, bundling and marking and more.

Product Features

- For handicrafts, repairing, fastening, bundling, strengthening, marking and much more
- For daily uncomplicated solutions and quick & easy repairs
- Very good adhesion to all types of surfaces
- Weather-resistant for in-and outdoor applications
- Tearable by hand
- Solvent-free

Application Fields

This Duct Tape works best on clean, smooth surfaces. Apply the tape and press firmly onto the surface.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|---------------------------|-------------------|--------|
| • Backing material | PE-film with PET-filament | • Total thickness | 215 µm |
| • Type of adhesive | synthetic rubber | | |



tesa[®] extra Power Universal

Product Information

Properties/Performance Values

• Tensile strength	46.3 N/cm	• Ozone resistance	yes
• Adhesive strength	High adhesion	• Residue free removal	no
• Ageing resistance (UV)	yes	• Reusable	no
• Application temperature from	10 °C	• Solvent free	yes
• Application temperature to	50 °C	• Spare part service	no
• Applicationfield	Garden, Garage, Car, Home	• Suitable surfaces	Even wood, Tiles, Most plastics, Glass, Metal
• Area of use	In- and Outdoor	• Tear resistance	yes
• Batteries included	no	• Temperature resistance	yes
• Batteries required	no	• Temperature resistance max.	95 °C
• Ecofriendly packaging	no	• Tensibility	19 %
• Hand tearability	yes	• UV-resistant	yes
• Hazard material	no	• Water resistance	yes
• Humidity resistance	yes	• Waterproof	yes
• Material	PE (polyethylene)	• Writable	no
• Oil and grease resistance	yes		

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>