



# **Product Information**

BNR 56622, 56623

## **Product Description**

For some tasks, an average repairing tape is simply not strong enough. Do not let small emergencies ruin your big adventures. tesa<sup>®</sup> Ultra Power Extreme Repairing Tape gives the needed extra strength. It is a versatile tape with extremely strong adhesion that can be used on many surfaces, smooth or rough. It is made for a variety of tasks such as patching holes, cracks, gaps, tears, and fixing broken parts. With its high UV- and temperature-resistance, it is suitable even for extreme weather.

## **Product Features**

- Powerful adhesion: Extremely strong hold for reliable fixing solutions in various challenging environments
- High Versatility: Thanks to its strong adhesive, the tape sticks perfectly even on rough surfaces
- Designed to last: Extra-durable due to its high abrasion resistance
- Extremely weather-resistant, waterproof, and UV-resistant for demanding outdoor tasks
- High-quality tool: The cloth-laminated backing makes this duct tape even stronger
- Easy to use: Highly convenient thanks to simple hand-tearability
- Multi-purpose repairing tape: Can be used both indoors and outdoors
- Convenient solution for fast emergency fixes: Ideal for repairing broken parts, can be used, e.g. to repair small damages on bumpers
- Fix your damage fast and reliably: Suitable for patching holes, cracks, gaps, and tears

#### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

#### **Product Construction**

•	Backing material	PET cloth	•	Total thickness	420 µm
•	Type of adhesive	natural rubber			





# **Product Information**

## **Properties/Performance Values**

<ul> <li>Tensile strength</li> <li>Abrasion resistance</li> <li>Adhesive strength</li> <li>Ageing resistance (UV)</li> <li>Applicationfield</li> </ul>	60 N/cm yes Very high adhesion yes Garden, Garage, Car,	<ul> <li>Oil and grease resistance</li> <li>Ozone resistance</li> <li>Residue free removal</li> <li>Solvent free</li> <li>Suitable surfaces</li> </ul>	yes yes no yes Most plastics, Glass,
Applicationnela	Home	Surable Suraces	Metal, Steel
<ul> <li>Area of use</li> </ul>	In- and Outdoor	Tear resistance	yes
<ul> <li>Batteries included</li> </ul>	no	<ul> <li>Temperature resistance</li> </ul>	yes
<ul> <li>Batteries required</li> </ul>	no	• Temperature resistance max.	90 °C
<ul> <li>Ecofriendly packaging</li> </ul>	no	Temperature resistance min.	-15 °C
<ul> <li>Hand tearability</li> </ul>	yes	UV-resistant	yes
<ul> <li>Hazard material</li> </ul>	no	Waterproof	yes
<ul> <li>Material</li> </ul>	PE (polyethylene)	Writable	no

#### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

