



tesa[®] Mounting Tape for Tiles & Metal

Product Information



BNR 77745, 77744

Product Description

Mounting Tape for Tiles and Metal is a permanent way to mount in damp rooms like bathrooms. It reliably holds mirrors and other objects of up to 4mm thick.

Product Features

- For smooth and solid surfaces like tiles indoors
- Suitable for damp rooms like bathrooms
- Specially suitable for mirrors and objects up to 4mm thick
- For permanent applications

Application Fields

- How to apply – Step by step
1. To ensure the best possible bond, use silicone-free alcohol or window cleaner to make sure both your surface and object are free of dust and grease. Ensure the surface is dry again before application.
 2. Check if the surface or the object is rougher and apply the mounting tape to rougher one. Apply the tape in vertical strips that correspond to the full length of the object. Reinforce the upper portion with shorter strips, since that's where the majority of the load will be born.
 3. Press down firmly over the entire surface of the Mounting Tape for at least five seconds.
 4. Remove the protective foil from the double-sided adhesive tape, taking care not to touch the exposed adhesive surface as this could affect the adhesion.
 5. Position the object and press it again firmly at least five seconds.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|---------|-------------------|---------|
| • Backing material | PE foam | • Total thickness | 1200 µm |
| • Type of adhesive | acrylic | | |



tesa[®] Mounting Tape for Tiles & Metal

Product Information

Properties/Performance Values

| | | | |
|--------------------------------|--------|-------------------------------|--|
| • Application temperature from | -10 °C | • Residue free removal | no |
| • Area of use | Indoor | • Reusable | no |
| • Batteries included | no | • Reusable with | _NULL |
| • Batteries required | no | • Solvent free | yes |
| • Chemical resistance | yes | • Suitable surfaces | Tiles, Most plastics, Glass, Metal, Steel |
| • Hazard material | no | • Temperature resistance max. | 40 °C |
| • Humidity resistance | yes | • Temperature resistance min. | 10 °C |
| • Oil and grease resistance | no | • UV-resistant | no |
| • Ozone resistance | no | • Waterproof | no |

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>