



tesa®

## Product Information

BNR 56496, 56497

### Product Description

Invisible repairs are challenging. tesa® Ultra Power Clear Repairing Tape supports you perfectly on all your adventures. It provides a convenient and discrete solution when it comes to fixing materials like plastic or glass. It has been developed for a variety of tasks such as patching holes, cracks, gaps, and tears. Due to strong adhesion, it can be used on many surfaces, even on rough and textile ones. Thanks to its high UV- and temperature-resistance, the tape withstands even extreme weather.

### Product Features

- Transparent tape for invisible repairs: Specifically developed for discrete repairs - the perfect fixing-solution for glass and plastic materials
- Powerful adhesion for reliable repairing: Very strong grip for fixing in diverse environments
- Multi-purpose: Thanks to its strong adhesive, the tape sticks perfectly even on rough or textile surfaces
- Developed to last: Durable due to its high abrasion resistance
- Suitable for outdoor jobs: Waterproof and extremely weather- and UV-resistant
- High Flexibility: The tape conforms to any shape and object
- Convenient and handy: Highly convenient thanks to its easy unwinding and its simple hand-tearing
- Universal application: Can be used both indoors and outdoors
- Multifunctional tape: Ideal for quick and lasting fixes, e.g. suitable for patching holes, cracks, gaps, and tears

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

- |                    |                  |                   |        |
|--------------------|------------------|-------------------|--------|
| • Backing material | PE film          | • Total thickness | 170 µm |
| • Type of adhesive | synthetic rubber |                   |        |



tesa®

## Product Information

### Properties/Performance Values

|                             |                              |                               |                                       |
|-----------------------------|------------------------------|-------------------------------|---------------------------------------|
| • Tensile strength          | 35 N/cm                      | • Ozone resistance            | yes                                   |
| • Abrasion resistance       | yes                          | • Residue free removal        | no                                    |
| • Adhesive strength         | Very high adhesion           | • Solvent free                | yes                                   |
| • Ageing resistance (UV)    | yes                          | • Suitable surfaces           | Most plastics, Glass,<br>Metal, Steel |
| • Applicationfield          | Garden, Garage, Car,<br>Home | • Tear resistance             | yes                                   |
| • Area of use               | In- and Outdoor              | • Temperature resistance      | yes                                   |
| • Batteries included        | no                           | • Temperature resistance max. | 90 °C                                 |
| • Batteries required        | no                           | • Temperature resistance min. | -10 °C                                |
| • Ecofriendly packaging     | no                           | • Transparency                | very good                             |
| • Hand tearability          | yes                          | • UV-resistant                | yes                                   |
| • Hazard material           | no                           | • Waterproof                  | yes                                   |
| • Material                  | PE (polyethylene)            | • Writable                    | no                                    |
| • Oil and grease resistance | yes                          |                               |                                       |

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>