



# tesa® 64911

## Product Information



### Product Description

tesa® 64911 is a double-sided PE-foam tape. Its high performance adhesive enables for primerless bonding of LSE- and MSE surfaces.

Developed for permanent mounting of similar and / or dissimilar plastic parts, tesa® 64911 has its main application in automotive module assembly such as park distance sensor bracket mounting.

tesa® 64911 features especially:

- High initial adhesion to LSE surfaces
- Highly conformable and gap filling
- Excellent converting properties

### Product Features

- High initial adhesion to LSE surfaces
- Highly conformable and gap filling
- Excellent converting properties

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

• Backing material	PE foam	• Colour	white
• Type of adhesive	synthetic rubber	• Colour of liner	red
• Type of liner	glassine	• Thickness of liner	71 µm
• Total thickness	1100 µm	• Weight of liner	82 g/m <sup>2</sup>

### Properties/Performance Values

• Elongation at break	254 %	• Tensile strength	16 N/cm
-----------------------	-------	--------------------	---------

### Adhesion to Values

• PP (initial)	16 N/cm	• Steel (initial)	17 N/cm
----------------	---------	-------------------	---------



# tesa<sup>®</sup> 64911

## Product Information

### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=64911>