



# tesa® 60960

## Product Information



## Durable and Scratch-resistant Floor Marking Tape

### Product Description

Our new tesa® 60960 Anti-Scratch PET Floor Marking Tape is a robust high-performance adhesive tape for permanent and long-lasting floor marking and warning applications. The abrasion-resistant, robust, and resilient marking tape combines a protective PET top layer, bright marking colors, and a synthetic rubber adhesive. The protective PET top layer improves the scratch, dirt, abrasion, and chemical resistance of the tape and ensures a long lifetime and permanent bright colors that don't wear off over time. Thanks to the synthetic rubber adhesive the anti-scratch floor marking tape adheres well on various smooth surfaces.

The bright colored tapes have a strong visibility for easy identification in areas of safety concerns and for warning purposes, a perfect solution for complementing 5S manufacturing initiatives. Depending on its color, the anti-scratch floor marking tape can be explicitly used as a warning tape. tesa® 60960 is available in the colors black, yellow, black-yellow, red, blue, green, orange, and white.

### Product Features

- Durable and abrasion resistant PET/PP laminate backing for permanent floor marking and warning applications.
- Protective PET top layer ensures long lifetime and permanent bright colors that don't wear off over time
- Bright colors ensure strong visibility for easy identification.
- Easier remodeling of warehouse areas compared to paint solutions

### Application Fields

- Permanent and long-lasting marking for high-traffic heavy-duty areas, at e.g. factories, warehouses, offices, or hospitals
- Marking of escape routes, passages or hazardous areas; withstands overrun from forklifts

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

- |                    |                  |                   |        |
|--------------------|------------------|-------------------|--------|
| • Backing material | PET film         | • Total thickness | 175 µm |
| • Type of adhesive | synthetic rubber |                   |        |

### Properties/Performance Values

- |                       |       |                    |          |
|-----------------------|-------|--------------------|----------|
| • Elongation at break | 140 % | • Tensile strength | 175 N/cm |
|-----------------------|-------|--------------------|----------|

### Adhesion to Values

- |         |          |
|---------|----------|
| • steel | 4.5 N/cm |
|---------|----------|

For latest information on this product please visit <http://l.tesa.com/?ip=60960>



# tesa<sup>®</sup> 60960

## Product Information

### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=60960>