



tesafilm[®] double-sided

Product Information



BNR 57911, 57954, 57910, 57912

Product Description

tesafilm[®] double-sided is a self-adhesive tape especially designed to stick paper, cardboard and photos

Product Features

- Double-sided adhesive
- Transparent
- Good adhesion
- High age-resistance
- Easy unwinding
- PP foil

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|---------------------|-------------------|-------|
| • Backing material | BOPP | • Total thickness | 75 µm |
| • Type of adhesive | water-based acrylic | | |

Properties/Performance Values

- | | | | |
|--------------------------|--------------------|--|------------------|
| • Tensile strength | 58 N/cm | • Photocopy neutral | no |
| • Adhesive strength | High adhesion | • Residue free removal | no |
| • Ageing resistance (UV) | yes | • Reusable | no |
| • Applicationfield | Office, Home | • Roll width max | 19 mm |
| • Batteries included | no | • Serrated blade | _NULL |
| • Batteries required | no | • Solvent free | no |
| • Ecofriendly packaging | _NULL | • Suitable for right and/or left handers | _NULL |
| • Hand tearability | no | • Suitable surfaces | Cardboard, Paper |
| • Hazard material | no | • Tear resistance | no |
| • Low noise unwinding | yes | • Tensibility | 80 % |
| • Material | PP (polypropylene) | • Transparency | medium |
| • Max roll length | 33 m | • Writable | no |



tesafilm[®] double-sided

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>