



tesa® PVC Embossed Plastering Tape

Product Information

BNR 55486

Product Description

tesa® PVC Embossed Plastering Tape is a high-quality tape, perfect for outdoor applications. The tape is made of sturdy PVC material. You can achieve straight tear-off lines thanks to the embossed backing. It can also be used to bundle other materials safely together or fix items in place. No traces are left behind, with excellent residue-free removal for up to 6 weeks. Achieve excellent looks and high-quality results with tesa® PVC Embossed Plastering Tape.

Product Features

- Ideal for outdoor applications which require high quality: Sticks safely to slightly rough surfaces
- * Versatile application: Has many uses – from masking and bundling to fixing
- * Strong and reliable: PVC backing material ensures durability and powerful adhesive performance
- * Durable: Can be applied in a wide temperature range and is heat- and mild cold-resistant
- * UV resistant for up to 6 weeks
- * Hand-tearable: The tape's embossed backing provides a straight tear-off plate – for straight edges, even when torn by hand
- * Avoid using masking tape directly on wooden floors

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|----------------|-------------------|--------|
| • Backing material | soft PVC | • Total thickness | 130 µm |
| • Type of adhesive | natural rubber | | |

Properties/Performance Values

- | | | | |
|----------------------|---------|----------------------|-----|
| • Tensile strength | 22 N/cm | • Batteries required | no |
| • Batteries included | no | • UV-resistant | yes |



tesa[®] PVC Embossed Plastering Tape

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>