

# tesafilm® eco & clear

## **Product Information**

BNR 57046, 04112, 56997, 57070, 57074, 57043, 57035, 57049, 57969, 57069, 57968

## **Product Description**

tesafilm® eco & clear, a 100% recycled self-adhesive transparent tape, environment friendly

#### **Product Features**

- Film and core made from 100% recycled plastic
- · Solvent free adhesives
- Transparent clear quality
- · Almost invisible on many surfaces
- · High age-resistance
- · Silent unwinding
- · Packaging: 80% recycled cardboard
- Suitable for use in all available tesafilm® dispensers
- The recycled content has been a approved by the independent certification organization DIN CERTCO belonging to the TÜV Rheinland (German technical control board).

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

#### **Product Construction**

•	Backing material	BOPP	•	Total thickness	52 μm
•	Type of adhesive	water-based acrylic			

### **Properties/Performance Values**

•	Elongation at break	20 %	•	Photocopy neutral	yes
•	Tensile strength	50 N/cm	•	Residue free removal	no
•	Adhesive strength	High adhesion	•	Reusable	no
•	Ageing resistance (UV)	yes	•	Roll width max	19 mm
•	Applicationfield	Office, Home	•	Serrated blade	_NULL
•	Batteries included	no	•	Solvent free	yes
•	Batteries required	no	•	Suitable for right and/or left	_NULL
•	Chemical resistance	no		handers	
•	Ecofriendly packaging	yes	•	Suitable surfaces	Cardboard, Paper
•	Hand tearability	no	•	Tear resistance	no
•	Hazard material	no	•	Tensibility	150 %
•	Low noise unwinding	yes	•	Transparency	good
•	Material	PP (polypropylene)	•	Unwind force n/cm	2.6 N/cm
•	Max roll length	33 m	•	Writable	no



# tesafilm® eco & clear

**Product Information** 

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

