




tesa[®] 88910 Optical Clear Adhesive



Product Information

250µm Optically Clear Adhesive for Automotive UV Block Applications

Product Description

tesa[®] 88910 OCA provides exceptional UV blocking performance, with a thickness of just 250µm. This OCA effectively protects all layers in the automotive display stack from harmful UV radiation, extending the longevity of sensitive automotive display components.

Product Features

- High UV blocking performance and excellent visible wavelength transmittance
- Meet crucial automotive standard test conditions
- Outstanding gap filling performance
- High transmittance and low haze
- Excellent temperature, humidity and UV resistance

Application Fields

tesa[®] 88910 OCA is suitable for optical lamination with,

- Soft OLED
- Polarizer
- Other functional films

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

• Backing	none	• Color	transparent
• Type of adhesive	acrylic	• Color of liner	transparent
• Type of liner	PET	• Thickness of easy release liner	75 µm
• Total thickness	250 µm	• Thickness of tight release liner	100 µm

Properties/Performance Values

• Ageing resistance (UV)	very good	• Haze	0 %
• Dielectric constant	4.68	• Refractive index	1.48
• Gap filling	12 %	• Transmittance (380 - 780nm) >	99 %

Adhesion to Values

• Glass (initial)	11.2 N/cm	• Polarizer (initial)	11.2 N/cm
-------------------	-----------	-----------------------	-----------

For latest information on this product please visit <http://l.tesa.com/?ip=88910>



tesa[®] 88910

Optical Clear Adhesive

Product Information

Storage Conditions

Storage Conditions

Temperature: From +15°C to +25°C

Relative humidity: From 40% to 70%

Precautions: Protect for direct sun light, do not store outside

Other storage advice: Storage of rolls in a horizontal position; Avoid mechanical impacts and short overheating, if removed from cold storage, ensure no condensation on packaging

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=88910>